

20.07 chains & thence run West, Var. 8° E. at 40.06 chains intersect North & South line through center of Section, 19 links North of 1/8 post.

Then from 1/4 Section post on line between Sections 16 & 21, East on Section line 20.11 1/4 to 1/8 Section post, Var. 8° 12' E, then random North & intersect East & West line through center of Section 4 links west of 1/8 Section post, True Variation of North & South line through center of S. E. 1/4, 8° 42' E. Thence corrected South & set post for corner to 1/16 Sections.

I hereby certify that the above is a true record of notes of said Survey  
John G. Clark  
Deputy County Surveyor

No 16

Notes of Survey made for Haynes Fitch of the S. E. 1/4 of the N. E. 1/4 of Section 16 Township 5 North Range 5 West June 28th 1853, William ~~Johnson~~ & Frederic N. Goodrich Chainmen & Markers, duly Sworn

Beginning at 1/4 Section post on line between Sections 15 & 16, ran thence a random line West at Var. of 8° 12' E. at 40.00 chains set temporary 1/4 Section post, thence continued West and intersect line between Sections 16 & 17, 65 links South of 1/4 Section corner, Thence from 1/4 Section corner on line between Sections 16 & 21, ran on a random line, Var. 8° 45' E, North to center of Section & intersect, corrected East & West line 26 links west of temporary center post, thence continued same line

North measuring from point of intersection, 20 40.26 chains to point in line 10 links East of 1/4 Section corner, Thence corrected South 20.13 chains & set stake, Then corrected & set post for 1/8 Section corner 20.15 1/4 chains East of post in center of Section & took bearing B. Val 8 S. 87 E. 132 links.

Then from 1/4 post on line between Sections 9 & 16, ran on a random line East, Var. 7° 25' E, at 40.31 chains intersect at corner to Sections 9, 10, 15 & 16, Thence correct West 20.15 1/2 chains & set 1/8 Section post, Then from corner of Sections 9 & 10, 15 & 16 run on a random line South, Var. 7° E, at 40.21 chains intersect 17 links East of 1/4 Section corner, Thence correct North 20.10 1/2 chains & set post for 1/8 Section corner.

Thence on a random line West Var. 7° 30' E, and intersect North & South line through center of Section 3 links South of 1/8 Section post, Then from 1/8 Section corner on line between the N. E. & S. E. 1/4 of said Section 16 run on a random line North at a variation of 8° 45' East, & intersect line between Sections 9 & 16 at 1/8 Section post, Thence corrected South on said line to point of intersection of said line with corrected East and West line through center of said N. E. 1/4 and set post for corner to 1/16 Sections.

A true record of notes of said Survey  
John G. Clark  
Deputy County Surveyor