

Field notes of Survey <sup>NO 17</sup> made for Page Blake of the W 1/2 of the S.W. 1/4 of Section 16, Township 5 North Range 5 West, June 28<sup>th</sup> 1853

Beginning at corner of sections 16, 17, 20 & 21 Random East var 8° 12' E. at 40.07 1/2 chains intersect 7 links North of 1/4 Section post between Sections 16 & 21. thence corrected West 20.03 1/2 chains & set post for 1/8 Section corner.

Then crossed the section through center from North to South, & also from East to West measuring West from intersection of true North & South line, making said West 1/2 40.08 chains, Corrected thence East 20.04 chains & set post for 1/8 Section corner.

Variation of East & West line through center of section 7° 44' E. Variation of North & South line through center of section 8° 49' E. Var. of West boundary of Section 16. 8° 46' East

A true record of notes of said Survey,  
John G. Clark  
Deputy County Surveyor

Survey made for William Young of the N.W. 1/4 and the N.W. 1/4 of the S.E. 1/4 of Section 16 of Township 5 North Range 5 West, June 28<sup>th</sup> 1853  
Frederic N. Goodrich & William Young Chainmen having been first duly sworn

Beginning at 1/4 Section post on line between Sections 15 & 16, run a random line thence West var. 8° 12' East, at 40. chains set temporary Stake and at 80. set temporary 1/4 Section corner.

Then from corner of sections 8, 9, 16 & 17, randomized South, var. 8° 55' E. at 40.84 chains intersect

East & West line through center (of Section) 29 links West of temporary 1/4 Section post, and at 80.37 chains intersect Section line 20 links East of corner to Sections 16, 17, 20 & 21. Thence corrected North 40.18 1/2 chains & set post for 1/4 Section corner

Then from 1/4 Section post on line between Sections 16 & 21 randomized North var. 8° 45' E, at 40.07 chains intersect true East & West line through center 2.6 links West of temporary 1/4 Section post, at 80.30 chains intersect 10 links East of 1/4 Section post on line between Sections 9 & 16. Thence corrected South 40.26 chains and set post for 1/4 Section corner.

Thence corrected South & set 1/8 post at 20.02 chains Then from 1/4 Section post in center of Section Corrected East 20.15 1/2 chains & set 1/8 post & took bearing B. oak 8 S. 82 E. 132 links. Then from 1/4

Section post on line between Sections 15 & 16, run a random line South var. 8° 45' E, at 40.14 chains intersect Section line 4 links East of corner to Sections 15, 16, 21, & 22. Thence correct North 20.07 chains & set 1/8 Section post. Thence random West, var 8° East

at 40.06 chains intersect North & South line through center of Section (19 links South of post set for 1/8 Section corner, Then from 1/4 Section post on line between Sections 16 & 21, East, var. 8° 12' E. 20.11 1/2 chains to 1/8 Section post.

Thence random North var 8° 45' E, and intersect 4 links West of 1/8 Section post set on East & West line through center of Section. Thence corrected South and set post corner to 1/16 Section in center of S.E. 1/4 of said Section 16.

A true record of notes of said Survey,  
John G. Clark  
Deputy County Surveyor

19 links mark (where) 20 links mark (where) 20 links mark (where)