

Not surveyed correctly of an acre

41 ^{NO 38} Surrey made Feb 16th 1854 by Albert C Stuntz
Deputy County Surveyor for Leola Buggs of the
N.W. 1/4 of Section 31 Township 6 North Range 5 West.
Commencing at the 1/4 Post on West Side of said
Section ^{which is 87 1/2 links north of the original corner set on range line & foot}
Section line a random line thence East through
Center of Section Variation 8° 40' East. Then correct
back ^{40 chains} ~~to 1/4 post~~ & set temporary quarter section
post in center of said section.
Then from 1/4 section post on North side of said
Section run a random South through the section
Then correct back North 1/2 way & set 1/4 post 40
chains west of East line of said section & took
bearing White Oak 18 N 38 W 16 1/2 links.

A true Record of the Notes of said Survey.
March 17th 1854. John G. Clark
County Surveyor

41A ^{NO 39} Record of Field Notes of Surrey made Dec 21st
1854 by Albert C Stuntz Deputy County Surveyor
in Section 22 Township 6 North Range 5 West for Haynes
Fitch William Fitch & William Heschlin.
Alfred Fitch and
Commencing at the 1/4 Section post on the South
side of said Section thence ran North Variation 9° East
at 40 chains set temporary 1/4 Section post at 61 chains
set temporary 1/16 Section corner at 81.13 intersect
Section line 100 links West of 1/4 Section corner.
Then from said quarter Section corner run West
at 20 chains set temporary 1/8 Section corner. at 40.11
chains intersect Section line 40 links South of Section
corner. Thence South at 20 chains set temporary
1/16 Section corner at 40.18 chains fell 4 1/2 links East
of 1/4 Section corner. Thence East through center of Section

at 20 chains set temporary 1/8 Section corner. at 60 chains
set temporary 1/8 Section corner. at 81.20 chains inter
sect Section line 51 links North of 1/4 Section corner
Thence corrected West 20.30 links & set 1/8 Section corner
Black Oak 20 N 31 E 87 links. White Oak 13 S 48 E 66 links
Then from 1/4 Section corner South side of said Section
22 ran East at 20 chains set temporary 1/8 Section corner
at 40.85 chains fell 7 links South of corner of Section
22. 23. 26 & 27. Thence corrected West 20.42 1/2 chains and
set 1/8 Section post. White Oak 18 N 67 W 117 links. White Oak
24 N 33 E 113 links. Thence North at 40.65 chains intersect
at 1/8 Section corner. Then corrected & set quarter section
corner in center of section at equal distances from North
& South boundaries & also at equal distances from East
& West boundaries of said Section (9). Black Oak 18
N 51 W 21 links. White Oak 10 S 38 E 38 links. Thence
corrected West 20.30 chains & set 1/8 Section corner. White
Oak 18 S 70 W 9 links. Thence North through center of N.W.
1/4 of said Section 22. at 40.42 chains intersect North
boundary of Section 18 links East of corrected 1/8 Section corner
Bearing to same (10). White Oak 10 S 18 E 99 links. Then corrected
1/16 Section corner on Section line on West side of said
N.W. 1/4 of said Section. Thence run East at 40.58 chains
fell 7 links South of true & corrected 1/16 Section corner. Bearing
to said corner (11). White Oak 12 N 59 E 83 links. Thence corrected
West 20.19 chains & set 1/16 Section corner at equal dis
tances from the North & South boundaries of said quarter
section. White Oak 18 N 9 E 42 links.

A true Copy of Notes of said Survey
Attest John G. Clark County Surveyor
Gave as to March 24th Grant County
A D 1854 Strong Lewis Wisconsin