



Corners	Bearing Trees	In. Dia.	Courses they Bear	Links Distant	REMARKS
3	Rock set by J.W. Blanding while one bearing tree was standing.				
4	White Ash Maple	15 12	N 53 E N 88 E	59 35	New bearing tree Original but now dead
5					Original bearings
6	Black Oak "	8 6	S 47 1/2 E S 8 1/2 W	5 14	Original bearings all destroyed but discernable
7	elm Willow Ash	25 25 12	S 15 1/2 E S 56 1/4 E S 15 W	251 284 214 1/2	Corner in middle of Slough - found by running the line between sections 10 + 15
9	Black Walnut Black Walnut	12 12	S 18 1/2 W S 54 W	134 164 1/2	This corner is equidistant between 5 + 7 (There being no Govt. quarter post between Sects. 9 + 10 Error in Government survey 1/4 corner between 9 + 10 by Major 9 57 1/2 W 112 1/2 S 53 1/2 E 36)
17	Black Oak Black Oak	26 8	N 61 E S 39 W	157 10	Equidistant from 6 to 9
20	Cottonwood Br. Oak	4 24	N 25 1/2 W N 58 E	163 213	Corner in Hull Slough Equidistant 3 to 17
22	Br. Oak Br. Oak	24 7	S 56 3/4 W S 10 W	297 126	Equidistant 17 to 20

STATE OF WISCONSIN, }  
GRANT COUNTY, } ss.

CERTIFICATE OF SURVEY.

I, Joel Barber, County Surveyor in and for the County and State aforesaid, do hereby certify that I have executed the Survey represented by the foregoing Plat and annexed Field Notes of Survey, in accordance with the State Laws and Instructions of the Commissioner of the General Land Office. Scale, 80 chains to 4 inches. The figures in red ink are the lengths of the lines as stated in the Field Notes of the Government Survey.

Declination of the Magnetic Meridian from the True Meridian ..... East. The variation of needle adopted in establishing corners is 8° 30' East.

WITNESS my hand this 26th day of December A. D. 18 76

J. J. Galway  
Edmund Welsh } CHAINMEN.

Joel Barber Co. SURVEYOR.