



Corners	Bearing Trees	In. Dia.	Courses they Bear	Links Distant	REMARKS
1					Bearings gone and indistinguishable - adopted a corner previously set by James Wilson.
2	White Oak	10	S 55 1/4 W	50	New bearing - the old ones dead
3	White Oak	8	S 14 1/2 W	28	Now - one original bearing remains
4					Original bearings yet remain
5	Black Oak Elm	20 12	N 70 1/2 E S 60 1/4 W	30 59	New bearings taken after running entire section line in accordance with corners 1 and 2 above.
9	White Oak Hickory	25 8	N 64 1/2 E S 42 E	29 61	
11	Bur Oak Black Walnut	12 1	N 31 1/2 E S 15 1/2 W	52 21	
12	Sugar tree Lynn	14 18	N 14 1/2 W N 58 1/2 W	35 44 1/2	
17	Black Oak Black Oak	12 6	N 34 1/2 E S 2 1/2 E	59 35	
21	Elm Black Oak	12 12	N 44 E S 83 W	38 28	
22	White Oak White Oak	12 12	N 32 1/2 W S 73 W	20 50	Surveyed Feb. 14 <sup>th</sup> 15 <sup>th</sup> + 16 <sup>th</sup> 1876
23	Butternut Sugar tree	12 14	N 64 1/2 E S 37 W	43 32	
18	White Oak White Oak	4 4	N 64 E N 42 W	8 1/2 12	
25	Black Oak	14	West	3 1/2	

CERTIFICATE OF SURVEY.

STATE OF WISCONSIN, }  
 GRANT COUNTY, } ss.

I, Joel Barber, County Surveyor in and for the County and State aforesaid, do hereby certify that I have executed the Survey represented by the foregoing Plat and annexed Field Notes of Survey, in accordance with the State Laws and Instructions of the Commissioner of the General Land Office. Scale, 80 chains to 4 inches. The figures in red ink are the lengths of the lines as stated in the Field Notes of the Government Survey.

Declination of the Magnetic Meridian from the True Meridian ..... East. The variation of needle adopted in establishing corners is 8° J.O. East.

WITNESS my hand this 9<sup>th</sup> day of January A. D. 1877.

Charles Wasmuth  
Ferdinand Martin } CHAINMEN.

Joel Barber Co. SURVEYOR.