



Corners	Bearing Trees	In. Dia.	Courses they Bear	Links Distant	REMARKS
---------	---------------	----------	-------------------	---------------	---------

State of Wisconsin }  
Grant County } S.S.

I, Charles Sampson, Surveyor in and for the County of Grant, State of Wisconsin do hereby certify that with the assistance of A. W. Appleby, Surveyor and Civil Engineer, I have this day surveyed the front line of Block 41 of the City of Boscobel, Wisconsin and established the North East corner of Lot 5 of said Block and have driven at said corner an iron stake 1/2 inch in diameter and 16 inches long said stake being 3 1/2 inches North of Stone foundation protruding from the building now owned by W. J. Graff

Nov. 3<sup>d</sup>, 1904  
Charles Sampson,  
Co. Surveyor  
A. W. Appleby

Recorded this 7th day of Oct. A. D. 1936  
CERTIFICATE OF SURVEY. attest: John T. Bue County Sur.

STATE OF WISCONSIN, }  
GRANT COUNTY, } ss.  
I, \_\_\_\_\_, County Surveyor in and for the County and State aforesaid, do hereby certify that I have executed the Survey represented by the foregoing Plat and annexed Field Notes of Survey, in accordance with the State Laws and Instructions of the Commissioner of the General Land Office. Scale, 80 chains to 4 inches. The figures in red ink are the lengths of the lines as stated in the Field Notes of the Government Survey.  
Declination of the Magnetic Meridian from the True Meridian \_\_\_\_\_ East. The variation of needle adopted in establishing corners is \_\_\_\_\_ East.  
WITNESS my hand this \_\_\_\_\_ day of \_\_\_\_\_ A. D. 18\_\_